

HAMMER

RRI-4596/1, RRI-4596R, RRI-4612K VL, RRI-4612R VL


IDEALLY SUITED FOR LONG TERM USE



CHISELS FOR AIR HAMMERS:

RRI-4596/1 & RRI-4612K VL


Shank size 22 mm
Hex x 82,5 mm



Order number	Description	L (mm) under the collar	B (mm)
MP4	Moil point	380	-
MP4-450	Moil point	450	-
NC4	Moil point	380	28
NC4-450	Flat chisel	450	28
CB4	Wide flat chisel	380	75
DC4	Asphalt chisel	400	80
AC4	Asphalt cutter	400	115

RRI-4596R & RRI-4612R VL

Shank size Ø 25 mm x 75 mm,
round collar 42 mm



Order number	Description	L (mm) under the collar	B (mm)
B350MP	Moil point	350	-
B450MP	Moil point	450	-
B350NC	Flat chisel	350	24
B450NC	Flat chisel	450	24

THE RED ROOSTER AIR HAMMERS have a high impact strength and a soft rubber D-handle that provides for optimum grip, so that you have perfect control over the hammer. They are vertically and horizontally suitable.

The versions for hexagonal chisels are fitted with a latch chisel holder. The versions for round chisels have a round screw cap as chisel holder.



The "VL" versions are by means of the internal suspension cylinder vibration reduced and therefore they can be used for extended time.

The RED ROOSTER hammers are equipped with an integrated lubrication system for a long life.

Type	Brand	Shank size mm	Bore diameter mm	Stroke mm	Blows p/min	J/Blow	Air. cons. l/s	Weight kg	Inlet thread	Hose diameter mm	Vibration m/s ²	Noise level dB(A)
RRI-4596/1	RRI	○ 22 x 82	34	114	1.590	51,6	15,0	10,6	PT 3/4"	13	16	101
RRI-4596R	RRI	○ 25 x 75	34	114	1.590	51,6	15,0	10,6	PT 3/4"	13	16	101
RRI-4612K VL	RRI	○ 22 x 82	35	170	1.290	81,2	16,6	12	PT 3/4"	16	3,8	105
RRI-4612R VL	RRI	○ 25 x 75	35	170	1.290	81,2	16,6	12	PT 3/4"	16	3,8	105